AUTEL®

MaxiCharger

AC Ultra Street







Power Sharing

OCPP Compliance

Weather Resistant

APP, RFID Card, Credit Card, Mobile Payment

One-Stop Cloud Network Management

8-inch HD Advertising Screen

Technical Specifications

Product Information

Charging mode	Mode 3
Input/output power rating and current	Three-phase up to 2*22kW/32A
Input/output voltage	400V±15%, three-phase; 50Hz
Network type	TT, TN, IT (Single-phase/Three-phase)
Connector type	IEC 62196 Type 2 Socket or Socket with shutter
Residual current detection	TypeA 30mA+ DC 6mA
Protection	Overcurrent, overvoltage, undervoltage, integrated surge protection
Card reader	ISO 15693, ISO 14443
Metering accuracy	± 1.0%; Build-in MID Certified meter; Eichrecht AC Meter(DE)

General Characteristics

IP and IK rating	IP54; IK10
Operating altitude	2000m
Operating temperature range	-30°C ~ +50°C
Storage temperature range	-30°C ~ +70°C
Mounting	Floor Standing
Dimensions (H×W×D)	1467 × 310 × 200 mm

User Interface

Status indication	APP/LCD (8 inch touch screen, 1280*720)
User interface	Autel Charge APP; Autel Charge Cloud
Connectivity	Wi-Fi, Ethernet, 4G, RS485
Communication protocols	OCPP 1.6J, OCPP 2.0.1
User authentication	APP, RFID card, Credit Cards (Optional)

Software Update

Software update	OTA updates via web portal

Certification and Standard

Safety standards	IEC/EN 61851-1, EN 62311, EN 62479, IEC/ EN 62955,NEN-EN-IEC 61439-7
Certification	CE; Eichrecht
Warranty	36 months, warranty extension possible

© Copyright 2024 Autel. All rights reserved. Specifications subject to change without notice.